

EasyCoat™

Acrylic protective coating for coils

EasyCoat™ is an acrylic coating aerosol, designed to guard air cooled coils against corrosive environmental factors such as acid rain, saline atmospheres and airborne ammonia. Its rapid-drying, waterproof, oil-resistant formulation ensures long-term protection for your air conditioning and refrigeration systems.

Specification			
Name	EasyCoat		
Product Code	EYCT1201		
Packing Quantity	12 x 500ml		and the second second
Packing Size (L x H x D) cm	21 x 25 x 27		
Shipping Weight (Kg)	7.7	evenssa. advance	
Shipping Volume (m3)	0.0145	iasyCoat	UNIVERSAL
Application	Acrylic coating for coils		
Soils	N/A	Manual Manual And	
Dilution (water:product)	NO	And the second s	
Contact Period	N/A		
Rinse/Flush Required	NO		
Special Features	Rapid Drying		
	Waterproof		
	Oil Resistant		

Directions for use

Turn system off. Isolate electrics. Clean coil to remove all contamination and grease – even if coil is new. Ensure coil is dry before proceeding. Spray EasyCoat[™] into coil, starting at top, then work methodically down and across. Wherever possible, treat both faces. EasyCoat[™] contains a faint dye that allows easy verification of coating.

I At each maintenance visit check coating is still intact. Reapply as required. If, due to I multiple reapplication, the coating is decreasing heat transfer, request Advanced I EasyCoat[™] Cleaner to remove all EasyCoat[™] – then start again.



Extremely Flammable - Harmful UN1950

Contains Toluene

R12: Extremely flammable. R38: Irritating to skin. R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation. R65: Harmful: may cause lung damage if swallowed. R63: Possible risk of harm to the unborn child. R67: Vapours may cause drowsiness and dizziness. S1/2: Keep locked up and out of the reach of children. S36/37/39:Wear suitable protective clothing, gloves and eye / face protection. S38: In case of insufficient ventilation, wear suitable respiratory equipment. S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label. S33: Take precautionary measures against static discharges. S23: Do not breathe spray. S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). S16: Keep away from sources of ignition - No smoking. Restricted to professional users.



advanced

Advanced Engineering Ltd Guardian House, Stroudley Road Basingstoke, Hants, RG24 8NL. UK Tel: +44(0)1256 460300 sales@advancedengineering.co.uk www.advancedengineering.co.uk

Consult Safety Data Sheet for full safety information. Always wear suitable PPE.



This product should only be used by trained operatives. The "directions for use" are recommendations only; correct use will depend upon circumstances. To the extent permitted, no liability can be accepted for loss resulting from its use. Advanced Engineering follows a policy of continual product improvement. For this reason, some materials and specifications could change without notice.