







# maxi orange

### **CONDENSATE REMOVAL PUMP**

Need more performance? Designed for larger units, the Maxi Orange pump gives you the extra power when you need it.





35L/h max. flow



15m max. rec. head (flow rate 10L/h)



35dB(A)

## **KEY FEATURES**

- High power motor
- Superior performance
- Submersible secondary reservoir included


# **SUITABILITY**





- Up to 46kW / 157,000Btu/h
- High wall split systems; Ducted units; Floor standing & Chassis units


✓ Perfect for... Large commercial units











MAXI ORA	NGE	SPECIFIC	ATIONS
love		2EI /b	@ 0 boo

MAXI ORANGE SPECIFICATIONS			
Max. flow	35L/h @ 0 head		
Max. rec. head	15m		
Max. suction lift	2m		
Sound level@1m	35dB(A)		
Power supply	230V AC 50-60Hz 0.1A*		
Rated	Non continuous		
Class	II appliance 🔲		
Max. unit output	46kW / 157,000Btu/h		
Max. water temp	40°C / 104°F		
Discharge tube	6mm ID		
IP Protection	IPX1		
Safety switch	3.0A Normally closed		
Thermal protection	✓		
Fully potted	✓		

#### **MAXI ORANGE OPTIONS**

Maxi Orange

\* Other voltages available

† Pump only

FP2210

cable • Reservoir • Reservoir lid with 1.5m
sensor cable • Submersible reservoir • Anti
siphon device • Float & filter • 1.5m Suction
tube 6mm ID • 220mm Orange inlet hose
14mm ID • 150mm Vinyl breather tube 6mm ID
• Drain connector kit • Fixing kit • Install manual

Maxi Orange pump • 1.5m Plug & play power

**IN THE BOX** 

Download manual at aspenpumps.com

View install video at aspenpumps.com

Description Part No. 1 Amp Fuse FP2620 Tube To Soil Stack FP2038 Adaptor Vinyl Tube Braided AX5100 1/4" (6mm) FP2640 Inline Filter 16mm



For more installation accessories take a look at our Aspen Xtra range



Self priming





