







CONDENSATE REMOVAL PUMP

With an impressive flow rate, these robust and reliable Heavy Duty pumps are perfect for the rapid removal of large quantities of condensate water.




HD6: 900L/h max. flow HD10: 1070L/h max. flow

HD6: 7m max. rec. head (flow rate 180L/h) HD10: 9m max. rec. head (flow rate 100L/h)

KEY FEATURES

- High flow rate
- Non return valve
- Easy installation
- 4 litre tank capacity




SUITABILITY

- HD6: Up to 1200kW / 4m Btu/h HD10: Up to 1460kW / 4.9m Btu/h

265mm

• Refrigeration cabinets; Humidifiers; Air handling units (AHUs)

300r



HEAVY DUTY 6 & 10 SPECIFICATIONS

HD6: 900L/h, HD10: 1070L/h

HD6: 7m, HD10: 9m

4L

HD6: 60dB(A), HD10: 64dB(A)

HD6: 230V AC 50-60Hz 1.5A

HD10: 230V AC 50-60Hz 0.38A

HD6: Non continuous

HD10: Continuous

I appliance

HD6: 1200kW / 4m Btu/h HD10: 1460kW / 4.9m Btu/h

40°C / 104°F


x2 40mm in,10mm out

IPX0

4.0A Normally closed

9

205mm − 150mm →



HEAVY DUTY 6 & 10 OPTIONS

4.3 kg

im •	150mm →
SUGGESTED XT	RA ACCESSORIES
Description	Part No.
Tank pump connector 16mm–21mm	FP2011
Tube To Soil Stack Adaptor	FP2038
Vinyl Tube Braided 1/4" (6mm)	AX5110
StayClean Tablets	FP2418
For more installation accessories take	

- a look at our Aspen Xtra range
- IN THE BOX Heavy Duty 6 or 10 pump • 2m power cable • Install manual

Download manual at aspenpumps.com

Information correct at time of going to press



Max. flow

Max. rec. head

Tank capacity

Power supply

Rated

Class

Sound level@1m

Max. unit output

Max. water temp

Inlet/outlet

IP Protection

Safety switch

Heavy Duty 6

Heavy Duty 10



FP2074/2

FP2066/2